

Neste Lubricating greases

Neste Superlix EP 2



12x 420 ml
Color: Blue

High-quality lubricating grease for vehicles

Meets or exceeds the following quality criteria:
DIN 51502: KP2N-30
ISO 12924: ISO-L-XC(F)DIB2
VOLVO Std 1277.2
NLGI GC-LB

- Good high temperature performance
- High dropping point
- Excellent mechanical stability
- Good anti-wear and EP properties

Product number	Density kg/m ³ +20 °C	NLGI hardness	Thickener	Drop point °C	Operating temperature range °C	Base oil viscosity cSt 40°C
725363	900	2	Lithium complex	>260	-30... +140	210

Applications:

- Wheel bearings and cardan joints
- Journal and roller bearings for industrial use
- All chassis lubrication points

Neste Superlix EM



12 x 420 ml
Color: Yellowish

Special grease for rolling bearings

Meets or exceeds the following quality criteria:
ISO 6743: ISO-L-XCDHB2
NLGI 2
DIN 51502: KP2N-30

- Good high temperature performance
- Excellent mechanical stability
- Good load carrying capability
- Good protection against corrosion

Product number	Density kg/m ³ +20 °C	NLGI hardness	Thickener	Drop point °C	Operating temperature range °C	Base oil viscosity cSt 40°C
703763	910	2	Lithium complex	>260	-30... +140	110

Applications:

- Electric motors
- Fast rolling bearings
- General lubrication

Neste Templex



12 x 420 ml
Color: Orange

High temperature grease

Meets or exceeds the following quality criteria:
ISO 12924: ISO-L-XC(F)DIB1.5
NLGI 1.5
DIN 51502: KP1.5N-30

- Wide operating temperature area
- Good anti-wear and EP properties
- Endures impact loads
- Good protection against corrosion

Product number	Density kg/m ³ +20 °C	NLGI hardness	Thickener	Drop point °C	Operating temperature range °C	Base oil viscosity cSt 40°C
701363	910	1,5	Lithium complex	>260	-30... +140	560

Applications:

- Slow plain and rolling bearings
- Bearings at high temperature
- General lubrication in hot areas

Neste Allrex EP 2



12 x 420 ml
Color: Yellowish brown

Grease for general use

Meets or exceeds the following quality criteria:
ISO 6743: ISO-L-XCCIB2
NLGI 2
DIN 51502: KP2K-30

MAN 283 Li-P 2
MB Blatt 267.0
Volvo std 1277.18

- Multiple applications
- Good pumpability
- Good antirust properties
- Good anti-wear and EP properties

Product number	Density kg/m ³ +20 °C	NLGI hardness	Thickener	Drop point °C	Operating temperature range °C	Base oil viscosity cSt 40°C
702263	950	2	Lithium	>180	-30... +120	200

Applications:

- General industrial lubrication
- General vehicle lubrication
- Agricultural machinery
- Construction machinery

Neste Allrex WR EP 2



12 x 420 ml
Color: Yellow

Water resistant universal grease

Meets or exceeds the following quality criteria:
ISO 12924: ISO-L-XC(F)CIB2
NLGI 2
DIN 51502: KP2K-30

- Excellent water resistance
- Good anti-wear and EP properties
- Very good protection against corrosion
- Multipurpose

Product number	Density kg/m ³ +20 °C	NLGI hardness	Thickener	Drop point °C	Operating temperature range °C	Base oil viscosity cSt 40°C
703463	910	2	Anhydrous calcium	>140	-30... +120	220

Applications:

- Agricultural, forestry and earthmoving machinery
- Damp or wet conditions
- General lubrication

Neste Lubricating greases

Neste MP Grease



12x 420 ml
Color: Light brown

General-purpose lubrication grease for vehicles

Meets or exceeds the following quality criteria:
ISO 12924: ISO-L-XC(F)CHB2
NLGI 2
DIN 51502: KP2K-30

- Multi purpose
- Good anti-wear and EP properties
- Good antirust properties
- Good adhesion to metal surfaces

Product number	Density kg/m ³ +20 °C	NLGI hardness	Thickener	Drop point °C	Operating temperature range °C	Base oil viscosity cSt 40°C
701063	900	2	Lithium	>180	-30... +120	110

- Applications:
- Wheel bearings
 - All chassis lubrication points

Neste OH Grease 2



12x 420 ml
Color: Red

Special grease for off-highway equipment

Meets or exceeds the following quality criteria:
ISO 12924: ISO-L-XC(F)CIB 2
NLGI 2
DIN 51502: KP2K-30

- Excellent adhesion on metal surfaces
- Good anti-wear and EP properties
- Good protection against shock loads
- Excellent water protection

Product number	Density kg/m ³ +20 °C	NLGI hardness	Thickener	Drop point °C	Operating temperature range °C	Base oil viscosity cSt 40°C
703263	900	2	Anhydrous calcium	>140	-30... +120	1380

- Käyttökohteet:
- Pivot pins for construction and logging machines and agricultural equipment
 - Vehicle chassis lubrication
 - Lubrication of slow speed journal and roller bearings
 - Not recommended for wheel bearings of vehicles

Neste OH Grease 0



12x 420 ml
Color: Red

Special grease for off-highway equipment

Meets or exceeds the following quality criteria:
ISO 12924: ISO-L-XD(F)CHB0
NLGI 0
DIN 51502: KP0K-40

- Excellent adhesion on metal surfaces
- Excellent pumpability also during wintertime
- Good protection against shock loads
- Excellent water protection

Product number	Density kg/m ³ +20 °C	NLGI hardness	Thickener	Drop point °C	Operating temperature range °C	Base oil viscosity cSt 40°C
703063	890	0	Anhydrous calcium	>120	-40... +120	1370

- Applications:
- Pivot pins for construction and logging machines and agricultural equipment
 - Vehicle chassis lubrication
 - Especially suitable for use in winter
 - Not recommended for wheel bearings of vehicles

Neste Allrex EP M3



12 x 420 ml
Color: Dark gray

Special grease containing Molybdenum disulfide

Meets or exceeds the following quality criteria:
ISO 6743: ISO-L-XCCIB2
NLGI 2
DIN 51502: KPF2K-30
MAN 285 Li-PF 2

- Good mechanical stability
- Extremely good load carrying capability
- Good protection against corrosion
- Multipurpose

Product number	Density kg/m ³ +20 °C	NLGI hardness	Thickener	Drop point °C	Operating temperature range °C	Base oil viscosity cSt 40°C
703363	970	2	Lithium	>180	-30... +120	200

- Applications:
- Heavy loaded slow moving bearings
 - Vibrating loads

Neste Molygrease



12x 420 ml
Color: Gray

Molybdenum disulphide grease

Meets or exceeds the following quality criteria:
ISO 12924: ISO-L-XC(F)CHB2
NLGI 2
DIN 51502: KPF2K-30

- Good for impacting loads
- Good anti-wear and EP properties
- Excellent antirust properties
- Good mechanical stability

Product number	Density kg/m ³ +20 °C	NLGI hardness	Thickener	Drop point °C	Operating temperature range °C	Base oil viscosity cSt 40°C
702563	910	2	Lithium	>180	-30... +120	110

- Applications:
- Motor vehicles, excavators, forest and earthmoving equipment
 - For objects with impacting loads
 - Ball joints and on sliding surfaces
 - Not recommended for lubrication of vehicle wheel bearings